

V1206-PDSS Zero Client Tera2 PCoIP® Portal Processor

Model Numbers: V1206-PDSS, V1206-PDSSF

Industry Leading Endpoint for VMware and Amazon Workspaces

The 10ZiG V1206-PDSS is part of our V1200 Tera2 PCoIP® Zero Client Series optimized for VMware and Amazon WorkSpaces environments. With no operating system and no local storage, the V1200 Series line provides an ultra-secure, yet powerful and easy-to-manage endpoint that eliminates the chance of viruses and provides extensive USB security and authentication features. Options ranging from dual through quad screen, PoE, Fiber, DVI-I, DVI-D, DisplayPort and Integrated SIPRNet Smart Card Reader with up to 6 USB 2.0 ports as well as standard TAA Compliance.

The V1206-PDSS model highlighted below comes equipped with 1 x DisplayPort, 1 x DVI-I, 6 x USB 2.0 along with an Integrated SIPRNet Smart Card Reader and optional Fiber support (SFP Ready). All V1200 Series PCoIP® Zero Clients by 10ZiG receive one year, free of the Desktop Access Subscription. The Desktop Access Subscription includes the PCoIP Management Console with a subscription to firmware and security updates as well as tech support.



▶ TERA2 PCoIP Portal Processor, Tera2321 PCoIP Chipset
▶ 1 x DisplayPort and 1 x DVI-I
▶ 6 x USB 2.0
▶ Integrated SIPRNet Smart Card Reader
▶ Optional Fiber Support (SFP Ready)
▶ TAA Compliant
▶ Optional VESA Mount
▶ 1 year free of to the Desktop Access Subscription

V1206-PDSS Zero Client

Tera2 PColP Zero Client Series



SPECIFICATIONS

1. Integrated SIPRNet Smart Card Reader
2. Line Out
3. Mic In
4. USB 2.0 (4)
5. Power Switch
6. Power / PColP Session LEDs
7. USB 2.0 (2)
8. RJ45 LAN Port (optional SFP Ready)
9. DVI-I
10. DisplayPort
11. DC Jack
12. Kensington Lock

System Specifications	
Management Utility	PCoIP Management
Processor	PCoIP® Portal Processor - TERA2
Chipset	TERA2321 PColP®
Dimensions	
Device	1.29"(H) x 4.96"(D) x 6.49"(W) - 33mm x 126mm x 165mm
Weight	1.49 lbs (.68 kg)
Connections	
Ports	6 x USB 2.0, 1 x DVI-I, 1 x DisplayPort, 1 x Mic In, 1 x Line Out, RJ-45 LAN (optional SFP Ready), 1 x DC Jack, 1 x Integrated SIPRNet Smart Card Reader
Video Resolution	1 Monitor at 2560 x 1600 or 2 Monitors at 1920 x 1200
Networking	
Ethernet	10/100/1000 Base-T
Fiber	Optional SFP Fiber Connector (100/1000Mbps) - V1206-PDSSF
Environmental	
Operating Temp.	32-104F (0-40C), 10-90% non-condensing humidity
Power	6 Watts, DC-12V/3A External Power Adapter
Certifications	
CE, FCC, CAN ICES-3/NMB-3, VCCI, UL, TUV-GS, C-Tick, GOST, BSMI, RoHS	



Americas
EMEA
APAC
DE

P: +1 (866) 865-5250
P: +44 (0) 116 214 8650
P: +61 2 80027421
P: +49 (0) 6724 9304-45

E: info@10ZiG.com
E: info@10ZiG.eu
E: info@10ZiG.com.au
E: vertrieb@10zig.de

W: www.10ZiG.com

